

GV-IO Box 16 Ports



The GV-IO Box 16 provides 16 inputs and 16 relay outputs. It supports both DC and AC output voltages, and provides a USB port for PC connection.

Specifications				
OS Supported	32-bit	Windows XP / Vista / 7 / 8 / Server 2008		
	64-bit	Windows 7 / 8 / Server 2008 R2 / Server 2012		
Compatible S/W	GV-System version 8.2 or above			
Input	Input	16		
	Input Signal	Dry Contact Wet Contact, 9-30V AC/DC		
Communication	Relay Output	16		
	Relay Status	Normal open		
	Relay Capacitance	USB Connection	30 VDC, 3A	
		RS-232 Connection	125 / 250 VAC, 3A 30 VDC, 3A	
Ethernet	RJ-45, 10/100 Mbps (Optional)			
DC IN	DC 12V, 1A			
Address	0-9, A-F			
Terminal Resistance	120 ohm			
Environmental Conditions	0 ~ 50 °C / 32 ~ 122 °F 5% ~ 95% (non-condensing)			
Dimensions (W x H x D)	180 x 27 x 183 (mm) / 7.09 x 1.06 x 7.2 (in)			
Installation Guide	GV-IO Box 16			

Note: All specifications are subject to change without notice.