


## GV-NET/IO Card V3.1



The GV-NET/IO card provides 4 inputs and 4 relay outputs. It supports both DC and AC output voltages and provides a USB port as well.

Specifications			
OS Supported	32-bit		Windows XP / Windows Vista / Windows 7 / Windows Server 2008
	64-bit		Windows 7 / Windows Server 2008
Input	Input		4
	Input Signal		Dry-Contact Wet-Contact : 9~30V AC/DC
Output	Relay Output		4
	Relay Status		Normal Open
	Relay Capacitance	USB Connection	30V DC, 3A
		RS-232 Connection	125 / 250V AC, 3A 30V DC, 3A
Interface			RJ-11 to DB9
			RJ-11 to USB
			3-pin internal USB to internal USB
Mode Switch	I/O Box Mode		Without GV-Video Capture Card
	NET/IO Card Mode		With GV-Video Capture Card
Address			1-4
Communication			RS-485, USB, RS-232
Environmental Conditions			0~50°C / 32~122°F , 5%~95% (non-condensing)
Dimensions (W x H)			90 x 99 ( mm ) / 3.90 x 3.54 (in)
Installation Guide			<a href="#">GV-NET/IO Card V3.1</a>

**Note:** All specifications are subject to change without notice.